

Solar cable H1Z2Z2-K



EN 50618
& IEC62930




Advantages

- EN50618 approval
- Double insulated Electron-beam cross-linked compounds
- UV, ozone and hydrolysis resistant
- Halogen free, flame retardant
- Flexible, easy to strip
- Compatible to all connectors
- Meter marking – easy installation

Applications

- Double insulated, electron-beam cross-linked cables for photovoltaic power applications.

Construction

- Conductor Tinned fine copper strands acc. to VDE 0295 / IEC 60228, Class 5
- Insulation XLPO, flame retardant, halogen free, electron-beam cross-linked
- Jacket XLPO, flame retardant, halogen free, electron-beam cross-linked
- Insulation color  black
- Jacket color  black or  red

Mechanical feature

- Bending radius 4 x outer diameters
- Temperature range -40 °C to +90 °C, Max. temp. at conductor +120 °C
- Short circuit temperature 250°C for 5 s
- Flame-resistant test acc. to EN 60332-1-2
- Anticipated service life 25 years

Electrical characteristics

- Rated voltage DC 1500 V
AC U₀/U: 1.0/1.0 kV
- max. permitted voltage U₀ 1800 V DC
- Insulation resistance 1000MΩ/KM
- Test Voltage (AC) AC 6.5kV, 50Hz, 5 min

Cross section nxmm ²	Conductor Ø mm	Outer Ø mm	Current-carrying capacity [A] at 60°C	Conductor resistance kΩ / km at 20°C	Weight app. kg / km	Cable Code
1x1.5	1.5	4.3	30	13.7	30	PV302515
1x2.5	2.0	5.2	42	8.21	42	PV502525
1x4.0	2.5	5.5	55	5.09	55	PV562940
1x6.0	3.3	6.3	70	3.39	68	PV842960
1x10.0	4.3	7.8	98	1.95	98	PV142301
1x16.0	5.3	9.2	132	1.24	132	PV228301
1x25.0	6.6	11.3	176	0.795	176	PV361302
1x35.0	7.8	13.3	218	0.565	218	PV525303
1x50.0	9.3	14.8	280	0.393	280	PV720305
1x70.0	11.4	16.9	350	0.277	350	PV988307
1x95.0	12.8	18.7	410	0.210	410	PV134930
1x120.0	14.6	20.7	480	0.164	480	PV169130

Dimensions and specifications may be changed without prior notice.

KUKA®

Shanghai KuKa Special Cable Co., Ltd
TEL: 0086-18317109559
Email: sales@kukacable.com

No.5878, Nanting Road, Jinshan District,
Shanghai, China
www.kukacable.com; www.kukaglobal.com