

SMART HOME CHARGING

NORA
Up to 22kW



# **Highlights**



## **Stress-free Installation**

Plug and Play!

Plug into the CEE socket or hardwire connection without opening the box.



## **Flexible Load Protection**

Flexible setting of power to ensure load safety and prevent tripping.

Dynamic Load Balancing and Solar Charging with Air DLM Kit, via wireless communication with NORA.



## **Smart Home Charging with APP**

Full control of your wallbox with RAEDIAN App.

### **Schedule Charging**

Schedule off-peak charging to lower charging cost.

#### InstaCharge

Start charging immediately at the maximum available current for once.

### **Charging Record**

Review and filter charging history, one tap to export record via email.

### **Share Your Charger**

One tap to share limited charging access with your family and friends.



## **Adaptive for Any Grid Supply**

CEE Adaptor for any location with any grid supply capacity and any socket.



## **Technical Specification**

**Power** 7kW / 11kW / 22kW

**Colors** 

Black / Woodgrain







**Feature & Function** 

Charging mode AC Mode 3

Charging connector IEC 62196 Type 2 cable, Type 2 socket

AC power output Single phase up to 7,4kW. Three phase up to 22kW with downgrade compatibility

Mounting options Wall mounted or pedestal

HMI Logo LED, Status LED

Load management Via App

Communication

Interface WiFi, BLE

User authentication RFID, App, Plug and Charge

Backend protocol OCPP 1.6 JSON
Software upgrade OTA via App, OCPP

**Electrical Design** 

Power supply Single phase: 230VAC ± 20%, 50/60Hz

Three phase:  $230/400VAC \pm 20\%$ , 50/60Hz

TN/TT/IT

Protection UVP, OVP, OCP, Relay Stuck, Over Temperature

Residual current protection Type A + 6mA d.c. per IEC 62955

Energy metering ±2% Accuracy

**General Design** 

Operating temperature -30°C to 55°C with derating mechanism

Operating altitude 2500m

Environmental rating Indoor and outdoor, IP65, IK10

Dimension 260x168x86 (mm)
Weight 2.1 kg (Socket Ver.)

#### **Certification & Standards**

IEC/EN 61851-1, IEC/EN 62955, IEC 61851-21-2

EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN 61000-3-11, EN 61000-3-12 EN 300 328 V2.1.1, EN 300 330 V2.1.1

## **Accessories**

CEE plug

Wall mounting screw

Cable gland

NORA wallbox

NORA CEE Ver.





## EU adapter pack 22kW

CEE 16A, CEE 32A, household plug (Type E/F, Type G, Type L)



Security screw

## EU adapter pack 7kW

Household plug (Type E/F, Type G, Type L)



## Charging cable 7kW/22kW

5m/7,5m, Type 2 to Type 2 Comes with a carry bag



### Pedestal with roof

For charging station mounting



### Air DLM kit

Wireless controller for dynamic load balancing and solar charging



### Cable hook

Convenient for keeping your charging cable organized